


Style No.:	UL2464	Specification:	12AWGx4C	Structure Figure	
<b>Item</b>		<b>Parameter</b>			
Conductor	Guage	12AWG			
	Material	Tinned Stranded Copper			
	Conductor Structure	TS65/0.25±0.007mm			
Insulation	Average Thickness	0.41mm			
	Minimum Thickness	0.35mm			
	Material	PVC			
	Diameter	3.20±0.10mm			
	No.	4C			
Assembly	Filler	/			
	Drain Wire	/			
	Aluminum Foil	/			
Braid Shield	Material	/		<b>Colour Code</b> Black, Brown, Red, Orange	
	Coverage	/			
	Overlap	/			
Jacket	Average Thickness	1.38mm		<b>Marking</b> UL AWM 2464 12AWG VW-1 ... CSA AWM 12AWG I/II A FT1 ...	
	Minimum Thickness	1.11mm			
	Material	PVC			
	Colour	Black			
	Overall Diameter	10.50±0.30mm			
<b>Electrical Characteristics</b>		<b>Physical Properties of Jacket</b>		<b>WCH CABLE INDUSTRIAL CO., LTD.</b> (86) 769-88649806   sales@wchcable.com	
1. Rated Voltage: 300V. 2. Conductor Resistance: 8.96Ω/km at 20°C. 3. Insulation Resistance: 10MΩ/km at 20°C.		1. Operation Temperature: 80°C.			