


Style No.:	UL2464	Specification:	24AWGx12C	Structure Figure	
<b>Item</b>		<b>Parameter</b>		 <p>Conductor</p> <p>Insulation</p> <p>Jacket</p>	
Conductor	Guage	24AWG			
	Material	Tinned Stranded Copper			
	Conductor Structure	TS11/0.16±0.007mm			
Insulation	Average Thickness	0.23mm			
	Minimum Thickness	0.19mm			
	Material	PVC			
	Diameter	1.10±0.10mm			
	No.	12C			
Assembly	Filler	/			
	Drain Wire	/			
	Aluminum Foil	/			
Braid Shield	Material	/		<b>Colour Code</b> Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Grey, White, White/Black, White/Brown	
	Coverage	/			
	Overlap	/			
Jacket	Average Thickness	0.89mm		<b>Marking</b> UL AWM 2464 24AWG VW-1 ... CSA AWM 24AWG I/II A FT1 ...	
	Minimum Thickness	0.72mm			
	Material	PVC			
	Colour	Black			
	Overall Diameter	6.20±0.30mm			
<b>Electrical Characteristics</b> 1. Rated Voltage: 300V. 2. Conductor Resistance: 94.2Ω/km at 20°C. 3. Insulation Resistance: 10MΩ/km at 20°C.		<b>Physical Properties of Jacket</b> 1. Operation Temperature: 80°C.		<b>WCH CABLE INDUSTRIAL CO., LTD.</b> (86) 769-88649806   sales@wchcable.com	
				DWG. NO.	REV
				WCH24642412BK001	A