

Style No.:	UL2464	Specification:	20AWGx10C	Structure Figure	
<b>Item</b>		<b>Parameter</b>			
Conductor	Guage	20AWG			
	Material	Tinned Stranded Copper			
	Conductor Structure	TS21/0.178±0.007mm			
Insulation	Average Thickness	0.24mm			
	Minimum Thickness	0.20mm			
	Material	PVC			
	Diameter	1.50±0.10mm			
	No.	10C			
Assembly	Filler	/			
	Drain Wire	/			
	Aluminum Foil	/			
Braid Shield	Material	/		<b>Colour Code</b> Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Grey, White	
	Coverage	/			
	Overlap	/			
Jacket	Average Thickness	1.06mm		<b>Marking</b> UL AWM 2464 20AWG VW-1 ... CSA AWM 20AWG I/II A FT1 ...	
	Minimum Thickness	0.84mm			
	Material	PVC			
	Colour	Black			
	Overall Diameter	7.60±0.30mm			
<b>Electrical Characteristics</b> 1. Rated Voltage: 300V. 2. Conductor Resistance: 36.7Ω/km at 20°C. 3. Insulation Resistance: 10MΩ/km at 20°C.		<b>Physical Properties of Jacket</b> 1. Operation Temperature: 80°C.		<b>WCH CABLE INDUSTRIAL CO., LTD.</b> (86) 769-88649806   sales@wchcable.com	
				<b>DWG. NO.</b> WCH24642010BK001	<b>REV</b> A