


Style No.:	UL2464	Specification:	22AWGx25C	Structure Figure	
<b>Item</b>		<b>Parameter</b>		 <p>Conductor</p> <p>Insulation</p> <p>Jacket</p>	
Conductor	Guage	22AWG			
	Material	Tinned Stranded Copper			
	Conductor Structure	TS17/0.16±0.007mm			
Insulation	Average Thickness	0.25mm			
	Minimum Thickness	0.21mm			
	Material	PVC			
	Diameter	1.30±0.10mm			
	No.	25C			
Assembly	Filler	Cotton			
	Drain Wire	/			
	Aluminum Foil	/			
Braid Shield	Material	/		<b>Colour Code</b>	
	Coverage	/			
	Overlap	/		Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Grey, White, White/Black, White/Brown, White/Red, White/Orange, White/Yellow, White/Green, White/Blue, ...	
Jacket	Average Thickness	1.05mm		<b>Marking</b>	
	Minimum Thickness	0.84mm			
	Material	PVC		UL AWM 2464 22AWG VW-1 ... CSA AWM 22AWG I/II A FT1 ...	
	Colour	Black			
	Overall Diameter	9.60±0.30mm			
<b>Electrical Characteristics</b>		<b>Physical Properties of Jacket</b>		<b>WCH CABLE INDUSTRIAL CO., LTD.</b> (86) 769-88649806   sales@wchcable.com	
1. Rated Voltage: 300V. 2. Conductor Resistance: 59.4Ω/km at 20°C. 3. Insulation Resistance: 10MΩ/km at 20°C.		1. Operation Temperature: 80°C.			