

Style No.:	UL2464	Specification:	22AWGx4C	Structure Figure	
<b>Item</b>		<b>Parameter</b>			
Conductor	Guage	22AWG			
	Material	Tinned Stranded Copper			
	Conductor Structure	TS17/0.16±0.007mm			
Insulation	Average Thickness	0.25mm			
	Minimum Thickness	0.21mm			
	Material	PVC			
	Diameter	1.30±0.10mm			
	No.	4C			
Assembly	Filler	/			
	Drain Wire	/			
	Aluminum Foil	/			
Braid Shield	Material	/		<b>Colour Code</b> Black, Brown, Red, Orange	
	Coverage	/			
	Overlap	/			
Jacket	Average Thickness	0.98mm		<b>Marking</b> UL AWM 2464 22AWG VW-1 ... CSA AWM 22AWG I/II A FT1 ...	
	Minimum Thickness	0.78mm			
	Material	PVC			
	Colour	Black			
	Overall Diameter	5.10±0.20mm			
<b>Electrical Characteristics</b>		<b>Physical Properties of Jacket</b>		<b>WCH CABLE INDUSTRIAL CO., LTD.</b> (86) 769-88649806   sales@wchcable.com	
1. Rated Voltage: 300V. 2. Conductor Resistance: 59.4Ω/km at 20°C. 3. Insulation Resistance: 10MΩ/km at 20°C.		1. Operation Temperature: 80°C.			