

Style No.:	UL2464	Specification:	22AWGx21C	Structure Figure
<b>Item</b>		<b>Parameter</b>		Please email (sales@wchcable.com) to get the complete structure figure.
Conductor	Guage	22AWG		
	Material	Tinned Stranded Copper		
	Conductor Structure	TS17/0.16±0.007mm		
Insulation	Average Thickness	0.25mm		
	Minimum Thickness	0.21mm		
	Material	PVC		
	Diameter	1.30±0.10mm		
	No.	21C		
Assembly	Filler	Cotton		
	Drain Wire	/		
	Aluminum Foil	/		
Braid Shield	Material	/		<b>Colour Code</b> Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Grey, White, White/Black, White/Brown, White/Red, White/Orange, White/Yellow, White/Green, White/Blue, ...
	Coverage	/		
	Overlap	/		
Jacket	Average Thickness	1.06mm		<b>Marking</b> UL AWM 2464 22AWG VW-1 ... CSA AWM 22AWG I/II A FT1 ...
	Minimum Thickness	0.85mm		
	Material	PVC		
	Colour	Black		
	Overall Diameter	9.00±mm		
<b>Electrical Characteristics</b> 1. Rated Voltage: 300V. 2. Conductor Resistance: 59.4Ω/km at 20°C. 3. Insulation Resistance: 10MΩ/km at 20°C.		<b>Physical Properties of Jacket</b> 1. Operation Temperature: 80°C.		<b>WCH CABLE INDUSTRIAL CO., LTD.</b> (86) 769-88649806   sales@wchcable.com  <b>DWG. NO.</b> WCH24642221BK001