

| Style No.: | UL2464 | Specification: | 24AWGx11C | Structure Figure | |
|--|---------------------|---|-----------|--|--|
| Item | | Parameter | | Please email (sales@wchcable.com) to get the complete structure figure. | |
| Conductor | Guage | 24AWG | | | |
| | Material | Tinned Stranded Copper | | | |
| | Conductor Structure | TS11/0.16±0.007mm | | | |
| Insulation | Average Thickness | 0.23mm | | | |
| | Minimum Thickness | 0.19mm | | | |
| | Material | PVC | | | |
| | Diameter | 1.10±0.10mm | | | |
| | No. | 11C | | | |
| Assembly | Filler | / | | | |
| | Drain Wire | / | | | |
| | Aluminum Foil | / | | | |
| Braid Shield | Material | / | | Colour Code Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Grey, White, White/Black | |
| | Coverage | / | | | |
| | Overlap | / | | | |
| Jacket | Average Thickness | 1.09mm | | Marking UL AWM 2464 24AWG VW-1 ... CSA AWM 24AWG I/II A FT1 ... | |
| | Minimum Thickness | 0.87mm | | | |
| | Material | PVC | | | |
| | Colour | Black | | | |
| | Overall Diameter | 6.20±0.30mm | | | |
| Electrical Characteristics 1. Rated Voltage: 300V. 2. Conductor Resistance: 94.2Ω/km at 20°C. 3. Insulation Resistance: 10MΩ/km at 20°C. | | Physical Properties of Jacket 1. Operation Temperature: 80°C. | | WCH CABLE INDUSTRIAL CO., LTD. (86) 769-88649806 sales@wchcable.com | |
| | | | | | |