

Style No.:	UL2464	Specification:	24AWGx26C	Structure Figure	
Item		Parameter		Please email (sales@wchcable.com) to get the complete structure figure.	
Conductor	Guage	24AWG			
	Material	Tinned Stranded Copper			
	Conductor Structure	TS11/0.16±0.007mm			
Insulation	Average Thickness	0.23mm			
	Minimum Thickness	0.19mm			
	Material	PVC			
	Diameter	1.10±0.10mm			
	No.	26C			
Assembly	Filler	/			
	Drain Wire	/			
	Aluminum Foil	/			
Braid Shield	Material	/		Colour Code Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Grey, White, White/Black, White/Brown, White/Red, White/Orange, White/Yellow, White/Green, White/Blue, ...	
	Coverage	/			
	Overlap	/			
Jacket	Average Thickness	1.26mm		Marking UL AWM 2464 24AWG VW-1 ... CSA AWM 24AWG I/II A FT1 ...	
	Minimum Thickness	1.01mm			
	Material	PVC			
	Colour	Black			
	Overall Diameter	9.00±0.30mm			
Electrical Characteristics 1. Rated Voltage: 300V. 2. Conductor Resistance: 94.2Ω/km at 20°C. 3. Insulation Resistance: 10MΩ/km at 20°C.		Physical Properties of Jacket 1. Operation Temperature: 80°C.		WCH CABLE INDUSTRIAL CO., LTD. (86) 769-88649806 sales@wchcable.com	