

Style No.:	UL2464	Specification:	26AWGx15C	Structure Figure
Item		Specification Value		Please email (sales@wchcable.com) to get the complete structure figure.
Conductor	Guage	26AWG		
	Material	Tinned Stranded Copper		
	Conductor Structure	TS7/0.16±0.007mm		
Insulation	Average Thickness	0.24mm		
	Minimum Thickness	0.20mm		
	Material	PVC		
	Diameter	1.00±0.10mm		
	No.	15C		
Assembly	Filler	/		
	Drain Wire	/		
	Aluminum Foil	/		
Braid Shield	Material	/		Colour Code Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Grey, White, White/Black, White/Brown, White/Red, White/Orange, White/Yellow
	Coverage	/		
	Overlap	/		
Jacket	Average Thickness	0.86mm		Marking UL AWM 2464 26AWG VW-1 ... CSA AWM 26AWG I/II A FT1 ...
	Minimum Thickness	0.69mm		
	Material	PVC		
	Colour	Black		
	Overall Diameter	6.20±0.30mm		
Electrical Characteristics 1. Rated Voltage: 300V. 2. Conductor Resistance: 140Ω/km at 20°C. 3. Insulation Resistance: 10MΩ/km at 20°C.		Physical Properties of Jacket 1. Operation Temperature: 80°C.		WCH CABLE INDUSTRIAL CO., LTD. (86) 769-88649806 sales@wchcable.com DWG. NO. WCH24642615BK001