

Style No.:	UL2464	Specification:	26AWGx30C	Structure Figure	
Item		Specification Value		Please email (sales@wchcable.com) to get the complete structure figure.	
Conductor	Guage	26AWG			
	Material	Tinned Stranded Copper			
	Conductor Structure	TS7/0.16±0.007mm			
Insulation	Average Thickness	0.24mm			
	Minimum Thickness	0.20mm			
	Material	PVC			
	Diameter	1.00±0.10mm			
	No.	30C			
Assembly	Filler	/			
	Drain Wire	/			
	Aluminum Foil	/			
Braid Shield	Material	/			Colour Code Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Grey, White, White/Black, White/Brown, White/Red, White/Orange, White/Yellow, White/Green, White/Blue, ...
	Coverage	/			
	Overlap	/			
Jacket	Average Thickness	1.09mm		Marking UL AWM 2464 26AWG VW-1 ... CSA AWM 26AWG I/II A FT1 ...	
	Minimum Thickness	0.87mm			
	Material	PVC			
	Colour	Black			
	Overall Diameter	8.50±0.30mm			
Electrical Characteristics 1. Rated Voltage: 300V. 2. Conductor Resistance: 140Ω/km at 20°C. 3. Insulation Resistance: 10MΩ/km at 20°C.		Physical Properties of Jacket 1. Operation Temperature: 80°C.		WCH CABLE INDUSTRIAL CO., LTD. (86) 769-88649806 sales@wchcable.com DWG. NO. WCH24642630BK001	
					REV A